

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Baker's Gray Away Wood Seal **HMIS CODES:** H F R P
PRODUCT CODE: Super Series, Cedar, Cedar Dark, Cedar Gold 2 2 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: TWP Coatings Inc.
ADDRESS: 1108 Summit Suite # 9 Plano, Texas 75074
EMERGENCY PHONE: 1-214-423-0211 **INFORMATION PHONE:** (972)-423-0211
DATE REVISED : 01-01-93 **NAME OF PREPARER :**

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mm Hg @ TEMP | WEIGHT PERCENT |
|--------------------------------------------|------------|------------------------------|-----------|-------|--------------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| SOLVENT NAPHTHA(PETROLEUM)MEDIUM ALIPHATIC | 64742-88-7 | 500PPM | 100PPM | | 5.0 100F | 20.0% |

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title 41 and of 40 CFR 372 are present. ***
THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING POINT: 323 Deg F **SPECIFIC GRAVITY (H2O=1):** 0.9
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
COATING V.O.C. : 1.46 LB/GL (175 G/L)
MATERIAL V.O.C.: 1.46 LB/GL (175 G/L)
SOLUBILITY IN WATER: NON SOLUBLE
APPEARANCE AND ODOR: DARK BROWN LIQUID

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 111 Deg F **METHOD USED:** TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0% UPPER: 7.0%
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES
ALL FIREFIGHTING PERSONNEL SHOULD BE WEARING FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS.
WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO COOL EXPOSED CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE
CONDITIONS TO AVOID
EXTREME HEAT

INCOMPATIBILITY (MATERIALS TO AVOID)
NONE REASONABLY FORESEEABLE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
CARBON MONOXIDE, CARBON DIOXIDE, SMOKE, OXIDES OF NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
NONE

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DANGER CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE. MODERATELY IRRITATING TO SKIN. MAY CAUSE ALLERGIC SKIN REACTION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY LEAD TO EXTRACTION OF NATURAL OILS WITH RESULTANT MILD IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE GASTROINTESTINAL IRRITATION. NAUSEA, VOMITING, AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

HEALTH HAZARDS (ACUTE AND CHRONIC)
CHRONIC EXPOSURE MAY CAUSE LIVER AND KIDNEY DAMAGE. OVEREXPOSURE MAY HAVE THE FOLLOWING EFFECT: CARDIAC ABNORMALITIES.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? YES
NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
NOT KNOWN

EMERGENCY AND FIRST AID PROCEDURES
INHALATION; MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY.
SKIN CONTACT; WASH WITH SOAP & WATER.
EYE CONTACT; FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.
INGESTION; DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT MATERIAL. TOXIC TO FISH. KEEP OUT OF PONDS, STREAMS, LAKES, AND ANY OTHER WATERWAYS.

WASTE DISPOSAL METHOD

DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP AWAY FROM HEAT. SPARKS AND OPEN FLAMES. CLOSE CONTAINERS AFTER EACH USE.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

ADEQUATE VENTILATION IS REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE.

VENTILATION

PROVIDE SUFFICIENT VENTILATION TO KEEP VAPORS CONCENTRATION BELOW GIVEN TLV AND LEL LEVELS.

PROTECTIVE GLOVES

REQUIRED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

EYE BATH AND SHOWERS SHOULD BE AVAILABLE. USE CHEMICAL RESISTANT APRON, BOOTS OR OTHER CLOTHING IF NEEDED TO AVOID REPEATED OR FREQUENT SKIN CONTACT. LIQUID MAY PENETRATE SHOES AND LEATHER CAUSING DELAYED IRRITATION.

WORK/HYGIENIC PRACTICES

WASH HAND BEFORE EATING, SMOKING OR USING WASHROOM.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, AMTECO, INC. DOES NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER.