



ACRYLPACK-S

kolour koat™ tint pack for solvent based acrylic sealer

www.SouthernStainAndSeal.com/Acrylpack



Acrylpack-S is a high solids, concentrated, solvent based acrylic tint system specially formulated for solvent based acrylic sealers. Acrylpack-S is formulated with high quality, ultra fine particle pigments that easily disperses in solvent based acrylic sealers. Acrylpack-S is a superior choice to obtain a semi-transparent stain or a solid opaque colored finish in most solvent based acrylic sealers.

Key Features & Typical Benefits

- 14 brilliant standard colors to choose from. (See Kolour Koat™ color chart) *Includes black & white
- Very economical, easy and decorative way to seal a variety of concrete substrates.
- Easily disperses into most solvent based acrylic sealers.
- Very easy way to create a beautiful, solid color concrete surface.
- Use in SurfKoat's 2000 Supreme, Stamp-Seal or any of our premium solvent-based acrylics.

Recommended Applications

- Effective on applications such as...
- Driveways
 - Patios
 - Sidewalks
 - Many other concrete surfaces where a solid color sealing and dust proofing method is desired.

Specifications / Compliances

Typical Properties & Technical Information	
PROPERTY	VALUE
Solids/Active Content, Percentage by weight	Concentrated (See sealer used)
Dry Time - Tack Free	Depends on sealers used
Dry Time - Foot Traffic	Depends on sealers used
Dry Time - Heavy Traffic	Depends on sealers used
Re-Coat Time Window	Depends on sealers used
Application Temperature	50° F - 80° F
VOC (Volatile Organic Compound) Content	N/A
Appearance - Wet	Depends on color chosen
Appearance - Dry	Tinted and Medium/High Gloss

Surface Koatings, Inc.
 134 Davis St. • Portland, TN 37148
 P: (615) 323-9461 • F: (615) 323-9816

Testing in accordance with procedures outlined in EPA Method 24, "Volatile Organic Content VOC of Paints and Related Coatings". The solids content was determined in accordance with ASTM D 5095 and the VOC was calculated in accordance with ASTM D 3960.

Kolour Koat™ is a trademark of Surface Koatings, Inc. • Refer to SDS prior to use.

Acrylpack-S

Application Instructions

SURFACE PREP: Concrete surface must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the sealer may have white spots and have premature delamination and failure.

Review the technical data and SDS for the chosen solvent based acrylic sealer prior to use for surface prep instructions, application instructions, coverage rates and limitations.

Substrate and air temperature must be no less than 40° F and not exceed 80° F. If applied outside these limits the sealer may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Note that in direct sunlight, substrate temperature can exceed 150° F which can cause extreme bubbling issues.

MIXING: Mix desired amount in a solvent based acrylic sealer for 1-2 minutes using a slow speed mixer prior to application. Allow any foam to settle prior to use. Material may separate during long term storage. Re-mix as needed.

USAGE RATE: Semi Transparent Stain: 2 - 6 ounces per gallon 10 - 30 ounces per 5 gallon
Solid Opaque Finish: up to 8 ounces per gallon up to 40 ounces per 5 gallon (typical usage is 32oz per 5gallon)

*Usage rates are suggested amounts only! Due to varying sealer compositions, substrates, surface texture, porosity and desired look a test area is recommended to achieve desired results.

APPLICATION: Review the technical data and SDS for the chosen solvent based acrylic sealer prior to use for surface prep instructions, application instructions, coverage rates and limitations.

FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS.

CAUTION: Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmenting may cause color float or streaking, especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 5 gallons of material for most opaque applications. For lighter colors it may take more and darker colors may take less depending on the application as well as the composition of the solvent based acrylic sealer.

Check Acrylpack-S for compatibility with the solvent based acrylic sealer to be used prior to use!

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. When applying, do not exceed 400 sq. ft. per gallon. Applying too thin of a coating may cause inadequate film formation or performance expectations may be limited. **DO NOT USE ON BRICK.**

Precautions and Limitations

- This product will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- If using indoor, use proper ventilation while applying and for hours after application to ensure fumes are removed.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product performs best when applied as one or two medium-light coats, not one heavy coat.
- Please be aware that this product when cured may be slippery when wet. An anti-slip additive, such as Surf-Grip, can be added to reduce slip hazards.
- This product is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin product. Improper thinning may cause sealer to delaminate in a short time frame.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use.
- Follow the instructions for the solvent based acrylic sealer that is to be used for application guidelines.
- SOLVENT VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

CLEAN-UP: Use xylene. Dispose of containers in accordance with local, state and federal regulations.

PRODUCT REMOVAL: Refer to sealer technical data sheet.

SHELF LIFE: Up to one year from manufacture date in its original, unopened container stored at room temperature.

PACKAGING: Available in 1 quart containers.

Always read all technical information, label and SDS prior to use. This information can be found online or by calling customer service at the number below.