

CITRUS DEGREASER

concentrated grease and oil stain remover

www.SouthernStainAndSeal.com/Concrete-Degreaser



Degreaser

designed to remove even the toughest deposits of dirt, grease,

Citrus

environmentally safe, citrus based,

concrete degreaser and cleaner

stains,

contaminating fluids from concrete

formulated to be used in exterior and

concentrated

other

and

Degreaser

Citrus

grime,

surfaces.

biodegradable,

oil






Key Features & Typical Benefits

- Pleasant citrus scent is less abrasive on the senses than many similar cleaners.
- Formulated as an economical, concentrated solution which can be diluted up to 1:10 with water.
- Safe for use with most mechanical scrubbing machines and cleaning equipment.
- Biodegradable solution that easily dissolves hydrocarbons such as grease and motor oils.

Recommended Applications

Effective on applications such as...

- Broom Finish Concrete
- Smooth Finish Concrete
- Pavers
- Driveways
- Sidewalks & Patios
- Garage & Warehouse Floors
- Many other concrete or masonry surfaces with tough stains that need to be removed.



Specifications / Compliances

Typical Properties & Technical Information	
PROPERTY	VALUE
Solids/Active Content, Percentage by weight	N/A
Dry Time - Tack Free	Refer to Directions
Dry Time - Foot Traffic	Refer to Directions
Dry Time - Heavy Traffic	Refer to Directions
Re-Coat Time Window	Refer to Directions
Application Temperature	50° F - 80° F
VOC (Volatile Organic Compound) Content	Not Applicable
Appearance - Wet	Transparent Orange
Appearance - Dry	N/A

Testing in accordance with procedures outlined in EPA Method 24, "Volatile Organic Content VOC of Paints and Related Coatings". The solids content was determined in accordance with ASTM D 5095 and the VOC was calculated in accordance with ASTM D 3960.

Citrus Degreaser Application Instructions

SURFACE PREP: Sweep the area to be cleaned free of trash and debris. Protect all areas not to be cleaned. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If needed, use a plastic or coated cardboard as a spray shield. Scraping off excess deposits may be necessary prior to application.

MIXING: Stir well before using. Material may separate during long term storage.

COVERAGE RATE: First Coat: 100 - 150 ft² per gallon* Optional Second Coat: 100 - 150 ft² per gallon*

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided. Please note that product can be diluted up to 1:10 with water yielding up to more than ten times the coverage rate per gallon purchased.

APPLICATION:

- 1. Use Citrus Degreaser straight for tough degreasing or dilute up to 1:10 with water for lighter duty cleaning.
- 2. Pre-wet the surface to be cleaned with clean water. Using a masonry wash brush, apply Citrus Degreaser at a rate of 100-150 square feet per gallon depending upon the porosity of the surface. When using on vertical surfaces, apply from the bottom to the top. Allow Citrus Degreaser to remain on the surface for approximately 20 minutes.
- 3. A stiff bristle brush should be used to work-in and agitate any heavily soiled areas to help break the bond from the substrate.
- 4. Flush the cleaned area with water. A commercial high PSI and GPM pressure washer is the recommended method of flushing the cleaned surface, however, a garden hose with high pressure spray head may work sufficiently.
- 5. Repeat process as necessary. For heavy stains still left in concrete, spot clean using Citrus Degreaser undiluted. Agitate and flush again to remove.

Please note: Although Citrus Degreaser is a biodegradable product, it may still pose a threat to plant life. Please test prior to use in areas where this may be an issue.

FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc.

Precautions and Limitations

- This product will freeze during storage. Store at temperatures above 40°F.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product may affect the surface of many new and existing concrete slabs. Test prior to use.
- This product is harmful if swallowed. Abide by recommended safety guidelines.
- This product is not a stripper and may not emulsify acrylic, epoxy, urethane, or any other coating.
- SOLVENT VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

CLEAN-UP: Use soap and warm water. Dispose of containers in accordance with local, state and federal regulations.

PRODUCT REMOVAL: Refer to directions.

SHELF LIFE: Up to one year from manufacture date in its original, unopened container stored at room temperature.

PACKAGING: Available in 1 gallon, 5 gallon and 55 gallon containers.

Always read all technical information, label and SDS prior to use. This information can be found online or by calling customer service at the number below.